

# Model 3P41

## Current Transformer Window Diameter 2.03”

### Application

3 phase relay, metering and motor overload protection.

### Frequency

50-400 Hz.

### Insulation Level

600 Volts, 10 kV BIL full wave.

Terminals are brass studs No. 8-32 with one flatwasher, lockwasher and regular nut.

Approximate weight 12 lbs.



(For Horizontal Mounting)

REGULATORY AGENCY APPROVALS



### Data Table: Model 3P41

Catalog Number	Current Ratio	V.A. ± 1% Class	ANSI Metering Class at 60 Hz					Secondary Winding Resistance ( $\Omega$ @ 75 °C)
			BO.1	BO.2	BO.5	BO.9	B1.8	
3P41-101	100:5	—	1.2	1.2	2.4	—	—	0.030
3P41-151	150:5	—	0.6	0.6	1.2	2.4	—	0.045
3P41-201	200:5	—	0.3	0.6	1.2	2.4	2.4	0.075
3P41-251	250:5	C10	0.3	0.3	0.6	1.2	2.4	0.094
3P41-301	300:5	C10	0.3	0.3	0.3	0.6	1.2	0.090
3P41-401	400:5	C10	0.3	0.3	0.3	0.3	0.6	0.151
3P41-501	500:5	C20	0.3	0.3	0.3	0.3	0.6	0.149
3P41-601	600:5	C20	0.3	0.3	0.3	0.3	0.6	0.179

# Model 3P41

