

Knife Switch Options

Optional Features

Designated Code

P Padlock Attachment

A padlock attachment and associated 90 degree stop are available on single throw switches only. Add the suffix – “P” to the catalog number.

A padlock attachment is available on double throw switches (lockable in open position only). Add the suffix – “P” to the catalog number.

F or T Handle Location

Single throw switches are available with the operating handle mounted on the *front* of the blade. Add the suffix – “F” to the catalog number.

Single or double throw switches are available with the operating handle mounted on *top* of the blade. Add the suffix – “T” to the catalog number.

M Auxiliary Knife Switch

An auxiliary, low-current knife switch actuated simultaneously with the main knife switch is available for remote indication purposes. Add the suffix – “M” to the catalog number.

L Auxiliary Limit Switch

An auxiliary, low-current micro-switch actuated simultaneously with the main knife switch is available for remote indication purposes. Add the suffix – “L” to the catalog number.

G Handle Guard

A optional handle guard can be provided on all switches. Add the suffix – “G” to the catalog number.

Z Field Discharge

Field discharge attachment, used when opening a generator field. Add the Suffix – “Z” to the catalog number.



Crompton Technology Inc.
7536 Bath Road
Mississauga, Ontario L4T 1L2
T (905)671-2304
F (905)671-3661
info@cromptoncanada.com
www.cromptoncanada.com

Tolerances $\pm .015$ for the hole diameters. Other tolerances $\pm .030$ unless specified.
Dimensions subject to change without notice.