

# Model 2DARL

Current Transformer  
Window Diameter 1.00"



## Application

Ammeters, wattmeters and cross current compensation.

## Rating Factor

1.0 @ 30°C. amb.

## Frequency

50-400 Hz

## Insulation Level

600 Volts, 10 kV BIL full wave

Flexible leads are UL 1015, 105 °C, CSA approved, #16 AWG, 24" long. Non-standard, lead length can be specified.

Approximate weight 0.9 lbs.



### REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI/IEEE C57.13.  
Classified by U.L. in accordance with IEC 44-1

## Data Table

Catalog number	Current Ratio	V.A. ±1% Class	ANSI Metering Class at 60 HZ			Secondary Winding Resistance (Ω@75 °C)
			B0.1	B0.2	B0.5	
2DARL-500	50:5	2% 2.5	4.8	—	—	0.008
2DARL-600	60:5	2.5	2.4	—	—	0.011
2DARL-750	75:5	3.5	1.2	2.4	—	0.015
2DARL-800	80:5	4.0	1.2	2.4	—	0.016
2DARL-101	100:5	5.0	1.2	2.4	—	0.018
2DARL-121	120:5	5.0	1.2	2.4	—	0.022
2DARL-1250	125:5	5.0	0.6	1.2	—	0.028
2DARL-151	150:5	10.0	0.6	0.6	—	0.031
2DARL-201	200:5	12.5	0.3	0.6	1.2	0.047
2DARL-251	250:5	15.0	0.3	0.3	0.6	0.074
2DARL-301	300:5	20.0	0.3	0.3	0.6	0.089

Model 2DARL

